

GL100

THE PERFECT SOLUTION TO CREATE PROFESSIONAL PERFORMANCES HOTSPOTS



Technical specifications

Network interface: n. 2 ports LAN 10/100Base-T Ethernet, RJ-45

Wireless interface: IEEE 802.11b/g (option n)

USB: 2 porte

Serial interface: RS232

Antenna: 3dBi omnidirezionale

VLAN: IEEE 802.1Q

Safety: WPA/WPA2 (802.11i)

Supply: 220 Vac 50Hz

Power supply: External 220Vac

Temperature: -5°C÷+65°C

Certification: CE, EN300328, EN301893, EN301489-1, EN301489-17, ROHS

Compatibility: tested compatibility with all certified Wi-Fi™ Certified

Dimension: 170 x 160 x 25 mm

Weight: 375 g

Leds: 3 leds (Status, Network, Activity)

Overview

The GL100 is a network gateway developed for handling the authentication of devices which have internet access. GL100 has been developed as a perfect client of the LUMEN authentication system of Guglielmo.

The GL100 can be used to authenticate every device, portable or not which has a valid account LUMEN by Guglielmo. It has a sophisticated encoding system based on the use VPN SSL and RADIUS, which guarantees the safety of every connection in according with WISP rules.

The GL100 is a self-installing product. When it is connected to internet it automatically proceeds to users authentication in accordance with the different policies of the service.

Main features

- Plug and Play device.
- Connected to internet contact the LUMEN by Guglielmo platform, it doesn't need the on site configuration.
- Radius client
- DHCP Server, DHCP Client, DHCP relay
- NAT (PAT) in LAN and WiFi interface
- Static routes support
- MULTIPLE SSID support in bridge on the VLAN
- Support n. 6 VLAN in according to the standard IEEE 802.1q
- Users authentication with captive-portal switchable on LAN, WiFi and selectively on the VLAN.
- Complete management AAA (Authorization, Authentication and Accounting
- Automatic redirection to the Multilanguage authentication page in https with valid SSL certificate (not self-generated).
- Web portal involved in authentication procedures customizable
- Authentication device on MAC address on remote central
- Authentication devices using local internal database
- Creation of tunnel VPN with central platform for service traffic : authentication, monitoring and management
- White list: list of reachable hosts defined as URL, IP or subnet address
- Black list: list of unreachable hosts defined as URL or IP address. Potentially different for every point. It is automatically and dynamically updated in centralized way.
- Internal list of banned devices or not authorized to browse
- Redirection after authentication to the requested web site or to other web site with configurable URL
- Bandwidth limiting for user
- Configurable integrated firewall
- Reachability from centralized platform by web or SSH, by tunnel VPN
- SNMP support
- Proxy HTTP integrated
- The supported wireless protocols are: IEEE 802.11 B/g (option n) with support of hidden SSID and WPA, WPA2 PSK, IEEE 802.1X for MT secure access
- Content filtering applicable to LAN, WiFi networks or if selected to the VLAN present.
- USB port for connection 3G/4G come back up XDSL or temporary Hot Spots.



Wireless Internet Service Provider

Guglielmo s.r.l.

Strada Parma 31/H, 43010 Pilastro di Langhirano (PR)

Guglielmo S.r.l. isn't liable and cannot be sue for document contents that could change without any notice.

All rights reserved.

All trademarks and registered trademarks are property of respective companies.

Copyright © 2012 Guglielmo

www.guglielmo.biz | info@guglielmo.biz

