## GL100M







## MAIN FEATURES

- VPN to Guglielmo Cloud
- Full Support of Layer 2 (switched) or Layer 3 (routed) connectivity to users devices
- Radius Client
- Complete management AAA (Authorization, Authentication and Accounting)
- DHCP Server, DHCP Client
- NAT (PAT)
- Static routes support
- Support of VLAN and IEEE 802.1q trunk
- Redirection to customized login portal
- Management and Authentication traffic on HTTPS with valid SSL certificate (not self-generated)
- White list: list of URLs, IP addresses or subnets reachable before the authentication, dinamically updated
- Black list: list of unreachable URLs or IP addresses, dynamically updated
- Internal list of banned devices, not authorized to browse
- Redirection after authentication to the requested web site or to other web site with configurable URL
  Bandwidth limiting for user
- Configurable integrated firewall
- Content filtering applicable
- Configurable traffic shaping
- Centralized platform for Firmware Upgrade

## TECHNICAL SPECIFICATIONS

| Chipset                 | MT7620A+7612E  |
|-------------------------|--|
| Protocol                | IEEE 802.11n, IEEE 802.11g, IEEE 802.11b,<br>IEEE 802.11a, IEEE 802.11ac   |
| RAM                     | DDR2 128MB (Max 256MB)   |
| Network Interfaces      | 1* 10/100M Auto MDI/MDIX LAN   |
| Wireless frequency band | 2.4G:2412 MHz-2484MHz (channel 1 -channel<br>14). 5.8G: 5725MHZ-5850M(channel:149, 15, 157,<br>161, 165)   |
| Wireless speed          | 2.4GHz, Up to 300Mbps, 5.8GHz, Up to 900Mbps   |
| LTE Module              | n. 1 LTE Module with 1 SIM card slot supporting 3G/4G up to 150 Mbit/s   |
| Flash                   | 16MB (Max 32MB)  |
| Light                   | Power, WLAN, LAN, 3G/4G, USB, 5G.  |
| Button                  | n. 1 reset button  |
| Power supply            | Input 12V 1A(9-28V)  |
| Antenna                 | 7 external 5dbi OMNI antennas (4 for Wi-Fi<br>antennas, 2 for 3/4g module antenna, 1 for<br>GPS antenna, the details need according to<br>customer's requirements) |
| Management              | Web Management   |
| Working temperature     | -20°C ~ 70°C   |
| Working humidity        | 10% ~ 90%RH non-condensing   |
| Storage temperature     | -40°C ~ 70°C   |
| Storage humidity        | 5% ~ 90%RH non-condensing  |
| Size                    | 12.5 x 10 x 2.5 cm   |
|                         |  |

## SERVICES

**LUMEN<sup>™</sup> module** provides extremely flexible services for the hotspot management, such as users authentication and policy enforcement.